

MastaLongset

BEDDING CEMENT

KNAUF

TECH DATA

MastaLongset is a plaster based cement for bedding tape into recessed edges and butt joints. It is also suitable for second coating plasterboard joints, internal and external angles and fastener heads. MastaLongset has an extended working time of 65 minutes with an 80 minute bucket set, making it particularly suitable for mechanical tools and ideally suited to larger jobs.

All Knauf jointing and finishing compounds can be used over MastaLongset as a final coat.



Performance

Mixing

Mixes to a smooth, creamy consistency by hand or electric mixer.

Trowelling

Very easy to trowel for both hand and mechanical tools, and has great body on the trowel and on the hawk.

Setting Time

Longer working time reduces frequency of mixes, resulting in more metres covered and less wastage.

Drying

Plenty of time to obtain good thin edges when feathering and re-trowelling as it does not dry out too fast.

Strength

A hard setting cement providing the strongest joint when used with paper tape.

Sustainable

Low VOC meeting sustainable building project requirements.

Benefits

- Free flowing
- Smooth edges
- Easy to re-trowel

Product Information

SIZE	20kg paper bag		
TYPE	Plaster based bedding cement		
MIXING RATIO	1L of water to 2kg of MastaLongset		
WORKING TIME	65 - 80 minutes		
SETTING TIME	80 minutes		
SYSTEM USAGE	<input checked="" type="checkbox"/> Bedding	<input checked="" type="checkbox"/> Second coat	
	<input checked="" type="checkbox"/> Standard	<input checked="" type="checkbox"/> Fire rated	<input checked="" type="checkbox"/> Wet area systems
VOC	<50g/L as VOC content per coating		

MastaLongset

BEDDING CEMENT



TECH DATA

Application

- MastaLongset is suitable for first and second coating on all internal lining applications, including fire rated and wet areas.
- Must not be applied over air drying compounds.
- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a thick, creamy consistency. Soaking is not recommended.
- Only mix enough cement to be used in 65 minutes, and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- Knauf strongly recommends the use of paper tape for jointing.
- Where fibreglass tape is used, the joint must be back-blocked with MastaBlock. Fibreglass tape must not be used in fire rated and wet area applications.
- Allow MastaLongset to set completely between coats.

Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring MastaLongset does not dry out before setting has taken place under severe hot dry conditions.



Quality
ISO 9001

SAI GLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit **knaufplasterboard.com.au** for details.

Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.